



## OTL193 19" Open-frame LCD Touchmonitor

### GeneralTouch's OTL193 open-frame LCD touchmonitor

GeneralTouch's OTL 193 open-frame LCD touchmonitor offers a cost-effective touch solution for systems integrators and OEMs, and facilitates those applications in retail, self-service and gaming or amusement markets. The OTL193 features a brilliant wide viewing angle panel which will instantly grab and hold the users' attention, whether they are checking out retail goods with a self-service kiosk or playing in a casino or arcade. As the whole enclosure is designed and manufactured to GeneralTouch's specifications, these open-frame monitors have a long-lasting product cycle life that bring continuity throughout the important phases of a project or an OEM customer design. It also features a unique dustproof or watertight sealing, making it an ideal choice for public and outdoor use.

The versatile OTL193 includes multiple mounting options, narrow borders with compactness, and a dual serial/USB touch interface with agency approvals.

#### Features:

---

- Cost-effective touch monitor solution
- Long lasting product cycle: mechanical parts controlled in house by GeneralTouch so that future upgrades do not bring external size changes
- Supplied with GeneralTouch's patented DustPro, WaterPro or SafeTouch Technologies
- Supplied with customized mounting brackets
- Fast touch response time
- Supplied with Serial or USB touch interface
- Multilingual and detachable On Screen Display (OSD)

#### Applications:

---

- Casino and gaming machines
- Amusement with pricing (AWP)
- Slot machines
- Video lottery machines (VLT)
- Kiosks
- Self-service terminals
- Industrial control

# Specifications

Model	OTL193
Display Type	19" Active Matrix TFT LCD
Case/Bezel Color	Black
Stand	No Stand
Aspect Ratio	5:4
Active Display Area	LCD Panel: 376.32mm(H) × 301.06mm(V)
Native Resolution (Typ.)	1280 × 1024 @ 60 Hz
Other Supported Resolutions	640 × 480 @ 60 / 72 / 75 Hz 640 × 480 @ 67 Hz 720 × 400 @ 70 Hz 800 × 600 @ 56 / 60 / 72 / 75 Hz 832 × 624 @ 75 Hz 1024 × 768 @ 60 / 70 / 75 Hz 1152 × 864 @ 75 Hz 1280 × 960 @ 60 Hz 1280 × 1024 @ 60 / 75 Hz
Pixel Response Time (Typ.)	5 ms
Colors	16.7 million
Brightness (Typ.)	LCD Panel: 250 cd/m <sup>2</sup>
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.) (from centre, CR>10)	Horizontal (left/right): 160° (80°/80°) Vertical (up/down): 160° (80°/80°)
Input Video Format	RGB Analog / DVI Video
Input Video Signal Connector	VGA / DVI-D
Input Frequency	Horizontal: 30 to 82 kHz Vertical: 50 to 75 Hz
Touch Technology	Surface Acoustic Wave (SAW)
Touch Interface	Dual Serial RS232 / USB
Touch Response Time	SAW: 10.4 ms
On Screen Display (OSD)	Control (back): Menu, Up, Down, Auto, Power
Power Supply	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ±5%
Input Connector	DC: Coaxial power jack (2.5 mm pin diameter, 5.5 mm barrel diameter, 11.5 mm barrel length)
Power Consumption (Max)	2CCFL: 30 W
Monitor Dimensions	Dust-proof (Standard): 425.5mm(W) × 349.5mm(H) × 48.2mm(D)
Shipping Carton Dimensions	530mm(W) × 460mm(H) × 195mm(D)
Weight	Monitor/Shipping (Approximately): 6.5kg / 10 kg
Mounting Options	Rear Mount, Side Mount, VESA Mount 75 mm & 100 mm
Sealing	Touchscreen sealed to bezel Touchscreen sealed to LCD panel
Temperature Range	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Relative Humidity (Non Condensing)	Operating: 20%-80% Storage: 10%-90%
Warranty	3 years LCD panel: 1 year MTBF: 50,000 hours demonstrated (Backlight Lamp Life, Hrs to ½ brightness)
Agency Approvals	FCC , CE , CCC

## MTBF (Mean Time Between Failures)

An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us

GeneralTouch Technology Co.,LTD reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.